



## (LG) Low-Gloss PAVER SEAL



1 US gal. • 5 US gal. • 55 US gal.

### SRW (LG) Low-Gloss PAVER SEAL

SRW (LG) Low Gloss Paver Seal™ sealer and sand stabilizer provides a clear, low-gloss, protective barrier that extends the life of your pavers and concrete surface. This barrier protects the pavers against elements which can stain and deteriorate their appearance, such as rust, oil, dirt, pool chemicals, salt and every day weathering. In one application, LG also stabilizes joint sand, adding protection against sand washout, weed growth and ant infestations. LG can be used as a curing and sealing compound on newly poured concrete.

- Low-gloss finish
- Breathable
- Protects joint sand from washout, weeds and ants
- Interior/Exterior
- Enhances, restores & protects
- Water-based

### DIRECTIONS

1. Thoroughly clean surface of joint sand, dust or loose material prior to application. Use SRW (EF) Paver Wash and Efflorescence Cleaner for general cleaning, paver prep and removal of efflorescence. If necessary, use SRW (CD) Cleaner/Degreaser for removal of stains and SRW (RE) Rust Eliminator for removal of rust.
2. Paver surface must be completely dry prior to sealer application. For newly poured concrete, apply immediately after surface water has dissipated and concrete can withstand weight. Recommended application temperatures are 50°F (10°C) to 80°F (27°C). Do not apply if inclement weather is forecasted within 24 hours.
3. **STIR THOROUGHLY PRIOR TO USE.** Product may settle. Do not dilute before applying. Can be applied with a sprayer or roller. For best results, apply with a clean, low pressure sprayer that is approved for solvent usage. Start at the highest elevation of the pavement. Immediately follow up by back rolling the sealer using a SRW Slit Foam Roller. This process will even out the application and prevent an uneven finish. Do not allow sealer to pool on the pavers or joints.
4. Allow sealed area to dry (24-hours). Protect from water and rain until dry. Dry-tack free: 25 minutes; Foot traffic: 24 hours; Vehicle traffic: 72 hours (Note: All calculations based upon 68-77°F (20-25°C). High humidity will increase drying time.

### USER TIPS

- A light purple/amber surface haze is common during the curing period.
- For more sheen, apply a 2nd thin coat, 4 hours after 1st coat. Do not over apply.
- For added slip resistance, use **SRW (SR) Slip Resistant Paver Grip**.
- Do not apply to structures under hydrostatic pressure.
- Care should be taken for vertical surface applications where runs may alter the finish.
- Not recommended for use on clay pavers, granite, bluestone and slate.

**Coverage:** Coverage: 100-150 sq. ft. per gallon, exterior pavement coverage (based on an 1/8" joint spacing). Quantity may vary depending on surface and application. Cleanup with soap and warm water.

## PACKAGING

PART NUMBER	SIZE	# PER CARTON OR PALLET	LBS
SSPS GAL / SSPS CTN	1 US Gallon	4/carton; 36 cartons/pallet	35/carton 1350/pallet
SSPS 5GAL	5 US Gallon	36/pallet	47/pail 1692/pallet
SSPS 55GAL	55 US Gallon	NA	485

## WARNINGS

**KEEP PRODUCT FROM FREEZING.  
KEEP OUT OF REACH OF CHILDREN.**

**Caution:** Protect buildings, landscaping and vehicles from overspray or spray drift.

**Storage:** Keep from freezing. Store container in a cool area, away from heat and open flame, with cap or lid firmly in place.

**Warning:** Do not inhale spray mist. Irritating to skin and eyes. In case of eye contact, flush with water for at least 15 minutes. Wash exposed skin with warm, soapy water. If irritation persists, see a physician. If ingested, do NOT induce vomiting. Dilute by drinking water. Seek medical attention. Always wear a mask and protective eyewear and clothing. **Keep out of reach of children.**

**Important Notice:**

Since the use of this product is beyond the control of the manufacturer, no guarantee or warranty, expressed or implied is made for the merchantability, fitness or suitability for the use of this product or otherwise extending beyond the description hereof except the obligation to replace that product for portion of shipment proved defective. Furthermore, nothing contained herein shall be construed as a recommendation to use any product in conflict with existing laws and/or patents covering any material or use. Liability is limited to product replacement only.